



**JP CONSULTANCY & ENGINEERING SDN BHD** (884518-A)  
NO 9 & 11, Jln Salung 33/26, Section 33, Shah Alam Technology Park, 40400  
Shah Alam, Selangor Malaysia. Tel 603 -51316514 Fax 603 -51210964  
Email: [mnara@jpconsultancy.com.my](mailto:mnara@jpconsultancy.com.my) / [enquiry@jpconsultancy.com.my](mailto:enquiry@jpconsultancy.com.my)

## PRODUCT DATA

# JP WRAP MC / LP



**JP WRAP MC / LP**  
(Moisture Cured / Low Pressure)

fiberglass cloth for corrosion, sealing, insulation, rehabilitation, waterproof protection, above & underwater

SUITABLE BASE MATERIAL  
Pipes, flanges, joints, valves, concrete, steel, wooden pilings, structural pilings, rods and cables

MAX TEMPERATURE : DRY = 120°C , WET = 70°C  
MAX PRESSURE : 20 BARS

SIZE : 2" x 1.5m

For Technical Inquiries, please contact  
**JP CONSULTANCY & ENGINEERING SDN. BHD**  
NO 9, JALAN SALUNG 33/26, SHAH ALAM TECHNOLOGY PARK, SEKSYEN 33,  
40400 SHAH ALAM, SELANGOR, DARUL EHSAN  
TEL : 603 - 5131 6514 FAX : 603 - 5121 0964 EMAIL :  
[ENQUIRY@JPCONSULTANCY.COM.MY](mailto:ENQUIRY@JPCONSULTANCY.COM.MY)

### DESCRIPTION

JP WRAP is a fiberglass cloth steeped with a water activated urethane resin and is used as a protective outer wrap in. JP WRAP offers exceptional mechanical and impact strength for under water, under ground and above ground corrosion protection coating.

### SUITABLE BASE MATERIAL

Pipes, flanges, joints, valves, concrete, steel, wooden pilings, structural pilings, rods and cables

### BENEFITS

- Excellent mechanical properties
- Resistant to temperature extremes
- Minimum surface preparation and ease of application
- Water, Acid, Salt and Soil Organics resistant
- Contains no solvent and VOC

Tensile Strength : 54,000 psi